

W = emgr (f, g, s, t, w, pr, nf, ut, us, xs, um, xm) ;

emgr – Empirical Gramian Framework (Version 5.0)

Mandatory Arguments

f	System Vector Field	(Handle)	$\mathbf{x} = \mathbf{f}(\mathbf{x}, \mathbf{u}, \mathbf{p}, t)$ i.e.: $\mathbf{f} = @(\mathbf{x}, \mathbf{u}, \mathbf{p}, t) \mathbf{A}*\mathbf{x} + \mathbf{B}*\mathbf{u} + \mathbf{F}*\mathbf{p}$;
g	Output Functional	(Handle)	$\mathbf{y} = \mathbf{g}(\mathbf{x}, \mathbf{u}, \mathbf{p}, t)$ i.e.: $\mathbf{g} = @(\mathbf{x}, \mathbf{u}, \mathbf{p}, t) \mathbf{C}*\mathbf{x} + \mathbf{D}*\mathbf{u}$;
		1	$\mathbf{y} = \mathbf{x}$
s	System Dimensions	(Vector)	$\mathbf{s} = [\mathbf{M}, \mathbf{N}, \mathbf{Q}]$ (Inputs, States, Outputs)
t	Time	(Vector)	$\mathbf{t} = [\mathbf{h}, \mathbf{T}]$ (Step, Stop)
w	Gramian Type	(Character)	
		'c'	Empirical Controllability Gramian (returns WC)
		'o'	Empirical Observability Gramian (returns WO)
		'x'	Empirical Cross Gramian (returns WX)
		'y'	Empirical Linear Cross Gramian (returns WY)
		's'	Empirical Sensitivity Gramian (returns {WC,WS})
		'i'	Empirical Identifiability Gramian (returns {WO,WI})
		'j'	Empirical Joint Gramian (returns {WX,WI})

Optional Arguments

pr	Parameters	(Vector)	Column Vector of System Parameters (Default: pr = 0)
		(Matrix)	Set of Parameter Column Vectors ('s','i','j' requires two)
nf	Options	(Vector)	Ten Components (Default: nf = 0), see Option Flags
ut	Input Function	(Handle)	Input function $\mathbf{u} = \mathbf{ut}(\mathbf{t})$
		1	Delta Impulse Input
		∞	Linear Chirp Function
us	Steady-State Input	(Scalar)	Uniform Steady-State Input (Default: us = 0)
		(Vector)	Individual Steady-State Input (J x 1)
xs	Steady State	(Scalar)	Uniform Steady State (Default: xs = 0)
		(Vector)	Individual Steady States (N x 1)
um	Input Scales	(Scalar)	Uniform Maximum Input Scales (Default: um = 1)
		(Vector)	Individual Maximum Input Scales (J x 1)
		(Matrix)	Custom Input Scales (J x *)
xm	Steady-State Scales	(Scalar)	Uniform Maximum Steady-State Scales (Default: xm = 1)
		(Vector)	Individual Maximum Steady-State Scales (N x 1)
		(Matrix)	Custom Steady-State Scales (N x *)

Option Flags

nf (1)	Trajectory Centering		
		0	None (Default)
		1	Initial State
		2	Final Steady State
		3	Arithmetic Average
		4	Root-Mean-Squared
nf (2)	Input Scale Sequence		
		0	Single (Default)
		1	Linear
		2	Geometric
		3	Logarithmic
		4	Sparse
nf (3)	State Scale Sequence		
		0	Single (Default)
		1	Linear
		2	Geometric
		3	Logarithmic
		4	Sparse
nf (4)	Input Transformation		
		0	Unit (Default)
		1	Inverse
nf (5)	State Transformation		
		0	Unit (Default)
		1	Inverse
nf (6)	Preconditioning		
		0	None (Default)
		1	Jacobi (Double Run)
		2	Steady-State Scaled
nf (7)	Non-Symmetric Cross Gramian (WX,WY,WJ only)		
		0	Off (Default)
		1	Non-Sym. Cross-Gramian
nf (8)	Extra Input		
		0	No Extra Input (Default)
		1	Parameter Perturbation Only
		2	State Perturbation Only
		3	State and Parameter Perturbation
nf (9)	Center Param. Scales (WS,WI,WJ only)		
		0	No Centering
		1	Arithmetic Mean Centering
		2	Geometric Mean Centering
nf (10)	Schur complement Options (WI,WJ only)		
		0	Detailed Schur-Complement (Default)
		1	Approximate Schur-Complement

Custom Solver

Global variable **ODE** to handle with signature:
y = solver(f,g,t,x,u,p); Default: RK - SSP32

Custom Inner Product

Global variable **DOT** to handle with signature:
w = kernel(x,y); Default: identity

Minimal Usage: W = emgr(f,g,s,t,w);

About Info: V = emgr('version');
